HyPanel Plus

Datasheet

New hassle-free smart control panel for your home

The akubela HyPanel Plus, a smart control panel with an Android 12 operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway and home automation, and is compatible with plentiful ecosystem. Multi-modal interaction can be easily used by the whole family, offering the excellent smart home experience.

At a Glance

- Excellent performance with Android 12 system
- 4" multi-touch screen with energy saving mode
- 2 touch buttons, suitable for the whole family
- 1-gang dimmer, can be directly connected to dimming lights
- Smart intercom, ZigBee gateway, home automation ALL IN ONE
- Kinds of sensors built-in

Basic Information

- Model Number: PS52V2-D1-US
- Power Supply: 100 ~ 260VAC, 50/60HZ
- Output: 400W total;

400W/220V/gang for resistive;

200W/110V/gang for resistive;

150W/gang for LED/CFL

- Operation System: Android 12
- RAM/ROM: 2GB/8GB
- Wi-Fi: WiFi6, IEEE 802.11a/b/g/n/ac/ax
- Bluetooth: Bluetooth 5.4
- Ethernet Port: 1×RJ45, 10/100Mbps adaptive
- ZigBee: ZigBee 3.0

- Microphone: Dual microphones, -26dBFS
- \bullet Speaker: Single speaker, $8\Omega/1.5W$

Appearance

- Material: Metal
- Button: 2 touch buttons
- Screen: 4" multi-touch screen
- Screen Resolution: 480×480 pixels
- Screen Brightness: 210 cd/m²

Sensors Built In

- Proximity Sensor: 30 ~ 60cm
- Light Sensor: Low-level lux detection
- Temperature Sensor: $\pm 1^{\circ}$ C, range: $-10 \sim 55^{\circ}$ C
- Humidity Sensor: ±5%, range: 10 ~ 90%RH, without condensation

Cakubela

10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061 Email: sales@akuvox.com Web: www.akubela.com



HyPanel Plus

Datasheet


Working Environment


- Environment: For indoor use only
- Working Humidity: 10 ~ 90%RH, without condensation
- Working Temperature: $-10 \sim 55^{\circ}C$
- Storage Temperature: -30 ~ 70°C


Installation


- Installation: Wall flush mounting
- Flush Mounted Module: US standard
- Wiring Way: L- + N- + Ground wire required

Product Dimension Diagram (mm)









6 TOP VIEW

🕜 akubela

10/F, No.56 Guanri Road, Software Park II , Xiamen 361009, China Tel: +86-592-2133061 Ext: 7694 Fax: +86-592-2133061 Email: sales@akuvox.com Web: www.akubela.com

Application Scenario

- Villas
- Apartment complexes
- Home automation systems
- Modern interiors

