

New hassle-free smart control panel for your home

The akubela HyPanel FANCOIL version, a smart fancoil thermostat control panel with an Android 10 operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway, Thermostat, and home automation, and it is compatible with plentiful ecosystem. Multi-modal interaction can be easily used by the whole family, offering the excellent smart home experience.

At a Glance

- Excellent performance with Android 10 system
- 4" multi-touch screen with energy saving mode
- Support 24V fancoil thermostat control
- Smart intercom, ZigBee gateway, home automation ALL IN ONE
- Kinds of sensors built-in
- EU standard flush mounted box



Basic Information

- Model Number: PS51-24VFANCOIL-EU
- Power Supply: 24VAC/DC
- Output: 5 relays with resistive load up to 5A, with inductive load up to 3A each;
 - 2 relays for cooling and heating valves ;
 - 3 relays for fan speed
- Operation System: Android 10
- RAM/ROM: 1GB/8GB
- Wi-Fi: IEEE802.11 b/g/n, @2.4GHz/5GHz
- Bluetooth: Bluetooth 4.2
- ZigBee: ZigBee 3.0
- NTC Measurement Range: -30 ~ 80°C
 - Accuracy: ±0.5°C

- RS485: Support
- Microphone: Dual microphones, -42dBV
- Speaker: Single speaker, 8Ω/1.5W

Appearance

- Material: V0 fireproof PC
- Screen: 4" multi-touch screen
- Screen Resolution: 480×480 pixels
- Screen Brightness: 210 cd/m²

Sensors Built In

- Proximity Sensor: 30 ~ 60cm
- Light Sensor: Low-level lux detection
- Temperature Sensor: ±1°C, range: -10 ~ 55°C
- Humidity Sensor: ±5%, range: 10 ~ 90%RH, without condensation

Working Environment

- Environment: For indoor use only
- Working Humidity: 10 ~ 90%RH, without condensation
- Working Temperature: -10 ~ 55°C
- Storage Temperature: -20 ~ 65°C

Installation

- Installation: Wall flush mounting
- Flush Mounted Module: EU/UK standard
- Wiring Way: L- + N- wire required

Application Scenario

- Villas
- Apartment complexes
- Home automation systems
- Modern interiors

Product Dimension Diagram (mm)

